


ADVANCED SERIES INL4128



INL4128 - 1080p- 5600 Lumens - 16:9 Aspect Ratio

The Quantum Laser Advanced Series is suitable for various applications, perfect for large venues, education, museums, houses of worship, and fixed installations. Advanced connectivity; dedicated HDBaseT and LAN ports, dual HDMI with 4K Ultra HD and HDR support and the added flexibility of a 1.6x optical zoom lens, 360 degrees, portrait and landscape orientation with complete corner alignment and adjustment.

Features

Lamp Free Environmentally-Friendly Laser Technology

Our Quantum Laser product line is reliable and environmentally friendly with solid-state laser light source technology. The complete product line is lamp, filter, mercury, and maintenance-free. The ultra-low energy usage for its class and long-standing durability and performance offers outstanding value and total cost of ownership.

Unparalleled Flexibility

Flexibility for almost every use model with a 1.6x optical zoom lens, front, rear, and ceiling placement and floor to ceiling projection, ceiling to floor, complete 360-degree installation across the horizontal axis, and not forgetting both landscape and portrait modes—ideal for meeting rooms, home office, classrooms, retail displays, fixed installations, bars, clubs, and restaurants and so much more.

Designed for maintenance-free 24/7 continuous operation

Designed for maintenance-free 24/7 continuous operation with advanced laser diode cooling and a IP5X rated dust resistant design.

SuperSmartProject

Our SuperSmartProject suite of power-saving, power optimisation, and utilisation features and functions combine ease of use and energy saving for your everyday use. Instant power on, signal power on, instant power off, auto power-off, 10 step illumination reduction, and Dynamic Black optimisation all help enhance your viewing experience while optimising energy usage.

Quantum Laser Engine

We incorporate laser phosphor illumination technology with blue laser diodes instead of traditional lamps to illuminate the Texas Instruments DLP digital micromirror device. The InFocus Quantum Laser engine produces vivid colours and exceptional image quality.

4K Ultra HD Support

Simply stunning image quality with up to 1920 x 1200 native resolution, HDMI 2.0 (HDCP 2.2) 4K Ultra HD and High dynamic range (HDR) support. The projected image has life texture details and improved image depth perception that pops off the screen.

Image

Projection Technology	Texas Instruments DLP®
Panel Size	0.65"
Native Resolution	1080p
Pixels	1920 x 1080
Aspect Ratio	16:9
Contrast Ratio	2000000:1
Brightness (Lumens)	5600
Light Source	Quantum Laser
Light Source Life Maximum Hours	30000
Maximum Supported Resolution	4096 x 2160
Horizontal Sync. Range (KHz)	15.4 ~ 91.1
Vertical Sync. Range (Hz)	24 ~ 120
Uniformity (%)	85

Optical

Lens	1.6x
Lens Zoom Adjustment	Manual
Optional Lenses	-
Image Offset (%)	113
Focal Length (mm)	20.91 ~ 32.62
F-Stop	-
Vertical Lens shift (%)	103 ~118
Horizontal Lens shift (%)	-
Keystone Adjustment	Automatic / Manual
Vertical Keystone Correction	±30°
Horizontal Keystone Correction	±30°
Projection Factor	1.4 ~ 2.24
Projection Distance (Meters/Feet)	1.0 ~ 9.3 / 3.3 ~ 30.5
Optical Zoom	Manual
Digital Zoom Demagnification / Magnification	0.8x ~ 2.0x
Focus Adjustment	Manual

Connectivity

Inputs	
Mini D-sub 15-pin (VGA)	✓ ✓
Composite Video	✓
S-Video	✓
HDMI™ 1.4	✓
HDMI™ 2.0	✓
USB-B 2.0	-
RJ45 - LAN 10/100/1000	✓
3.5 mm Stereo Mini Jack	✓
3.5 mm Stereo Mini Jack with Microphone	✓
‘s	
↵-sub 15-pin (VGA)	✓

3.5 mm Stereo Mini Jack	✓
Powered USB-A for Wireless Dongle	✓
3D Sync	-
Other	
RS232	✓
RJ45 HDBaseT	✓
All Major 3D Formats	✓
USB-B 2.0 for Service	-
USB-A for Service	-
Micro USB for Service	-
Document Reader	-
Video Player	-
Photo Viewer	-
Music Player	-
12v Screen Trigger	-

Power

Power Supply	100 ~ 240 V AC; 50 - 60 Hz
Power Consumption Max (W)	341
Power Consumption Min. (W)	190
Power Consumption Network Standby (W)	<2.0
Power Consumption Standby (W)	<0.5

General

Dimensions (W x H x D) (mm / in)	374 x 117 x 302 / 14.7 x 4.6 x 11.9
Product Weight (Kilograms/Pounds)	5.5 / 12.1
Fan Noise (dB)	28 ~ 30
Audio (w)	1x 10
Operating Temperature (Celsius/Fahrenheit)	5 ~ 40 / 41 ~ 104
Operating Humidity (%)	10 ~ 85
Max Operating Altitude (meters / feet)	3048 / 10000
Storage Temperature (Celsius/Fahrenheit)	-0 ~ 40 / 32 ~104
Storage Humidity (%)	0 ~ 95
Security	Kensington Lock Port™, PIN & Timer
In the Box	Projector, IR Remote Control (no Batteries), Power Cord, VGA Cable, Projector, Setup Guide, Lens Cap
Safety and Regulatory	CE, EAC, RoHS, cTUVus, CCC, FCC, FDA, NOM
Environmental	WEEE, RoHS

Copyright © 2022, InFocus and its logo is a registered trademark of InFocus Corporation. Maxnerva Technology Services Limited is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted; all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.