MAX BR1 Slim Portable and Rugged 4G LTE Router





The MAX BR1 Slim is compact $(1.1 \times 3.8 \times 4.8 \text{ inches})$ and tough enough to install just about anywhere, and it offers advanced features such as GPS fleet tracking, remote management, and USB or terminal block power capability.

Compatible Wi	ith:		
verizon	Sprint	🥰 at&t	T - Mobile
	TELUS	Bell	U.S . Cellular



Redundant SIM Slot for Multiple Carriers

Redundant SIM slot with automatic switching for reliable network. You can also set the MAX BR1 Slim to automatically switch SIM cards when you're in danger of exceeding a data cap. It also allows you travel across borders without changing SIM cards manually.



Dual Micro USB Power Input

Connect one of the two built-in 5V micro USB ports to a 10000mAh power bank for up to 7 hours of operation. Running low on power? Connect a second power bank before disconnecting the first for uninterrupted networking.

SpeedFusion

*Selected models

SpeedFusion Hot Failover.

The MAX BR1 Slim automatically re-establishes your SpeedFusion VPN connection on lower priority link when your primary WAN fails. Your VPN stays up, and you stay seamlessly connected.



Fleet Tracking and Management

Track and manage your fleet from anywhere. With built-in GPS and InControl 2 cloud-based management, you can keep tabs on location and manage your mobile network from any Internet-connected device.



Customize Captive Portal

Branding your captive portal is as easy as uploading your logo and terms & conditions. You can easily set bandwidth allowance and access duration per user or manage access using RADIUS or LDAP servers.



Ultra-Portable LTE Connectivity

The MAX BR1 Slim gives you full-featured LTE Connectivity in a package that measures just $1.1 \times 3.8 \times 4.8$ inches. Its rugged metal enclosure stands up to moisture, dust, and vibration. It gives you and your devices, such as surveillance camera, LTE connectivity anywhere.

Specifications	MAX BR1 Slim	
WANInterface	1x FE 1x Embedded LTE-A Modem with Redundant SIM Slot	
LAN Interface	1x FE	
Wi-Fi Interface	802.11b/g/n 150Mbps Wi-Fi WAN or AP	3.8 inches
Router Throughput	100Mbps	3.8 inches 120mm 97mm
Recommended Users	60	Terminal
LTE Modem	Downlink/Uplink Datarate: 100Mbps/50Mbps	Block
LTE-A Modem	Downlink/Uplink Datarate: 300Mbps/50Mbps	
Cellular and GPS Antenna Connector	2x RP-SMA Cellular Antenna Connector 1x SMA GPS Antenna Connector 1x SMA Wi-Fi Antenna Connector	
Power Input	Micro USB 5V 2A/Terminal Block: 10V – 24V DC	5V 2A FE LAN FE WAN Micro USB Input
Power Consumption	10W (max.)	SMA GPS RP-SMA V
Dimensions	1.1 x 3.8 x 4.8 inches 27 x 97 x 120 mm	Antenna Connector Antenna Cor
Weight	0.8 pound 350 grams	
Operating Temperature	-40° – 149°F -40° – 65°C	
Humidity	15% – 95% (non-condensing)	SMA Cellular Redundant
Certifications	FCC, CE, RoHS, E-Mark, IC EN 61373:1999 IEC 61373:1999 : Shock and Vibration Resistance EN 50155: Railway Applications EN 61000: Electromagnetic Compatibility	Antenna Connector SIM Slot
Warranty	1-Year Limited Warranty	

Ordering Information

	-					
	Product Code	Carrier/Region	Embedded Modem	4G Bands	3G Bands	
4G LTE	MAX-BR1-Slim-LTE-E-T	Europe/International	1	4G LTE: B1, B3, B5, B7, B8, B20, B38 (TDD), B40(TDD), B41 (TDD)	WCDMA/HSPA+/DC-HSPA+: B1, B5, B8	
	Feature Add-On					
	Product Code	Feature Pack	Description			
	MAX-BR1-ADV	Advanced Feature Pack	Package includes a software license key for Advanced Car-Fi Roaming; and SpeedFusion and IPsec X.509 Certificate Support			
	PVN-LC-05	PepVPN License Key for Velocity and BR1 family	Enables up to 5 PepVPN connections			

MAX-BR1-ADV Advanced Feature Pack Enables up to 20 PepVPN connections

Features

WAN

Support for PPPoE, Static IP, DHCP WAN Link Health Check Bandwidth Allowance Monitor Support for Dynamic DNS services WAN Port Convertible into LAN Port

LAN

DHCP Server for LAN Clients Extended DHCP Options DHCP Reservation DNS Proxy for LAN Clients VLAN on LAN Support Port-Based VLAN

Security Stateful Firewall

^ Feature is available as an upgrade

peplink PEPWAVE

DoS Prevention Web Blocking Web Filtering Blacklists

Complete VPN Solution PepVPN / SpeedFusion Hot Failover Site-to-Site VPN Hot Failover 256-bit AES Encryption Pre-shared Key Authentication Dynamic Routing X.509 Certificate Support^ IPsec VPN (Network-to-Network)

Networking NAT and IP Forwarding Static Routes Port Forwarding Many to One, One to One NAT NAT Pool SIP ALG, H.323 ALG UPNP, NAT-PMP BGP, OSPFv2 and RIPv2 Support

Advanced QoS Individual Bandwidth Limit Application Prioritization SIP, HTTPS, VPN QoS Custom Application QoS

Device Management InControl 2 Cloud Managment Router Utility Mobile App Active Client & Session Lists Bandwidth Usage Statistics Web Reporting Services Syslog Service SNMP v1, v2c and v3

Global Positioning System

Integrated GPS Device Location Map Location Tracking Data Fleet Management with InControl 2

Package Content MAX BR1 Slim

1x 5dBi Wi-Fi Antenna 1x GPS Antenna 2x 2dBi 4G LTE Antennas

> **www.pepwave.com** ©Pepwave. All rights reserved.

1.1 inches 27 mm

Ref no.: max-br1-slim-201906-v7